

Tough, Durable and Waterproof Interior Moulding that Works Like Wood



Available in the following patterns:

- | | |
|-------------------|----------|
| • Quarter Round | TIM 105 |
| • Base Shoe | TIM 127 |
| • Base | TIM 623 |
| • Streamline Base | LTIM 726 |
| • Casing | TIM 356 |
| • Crown | TIM 49 |
| • Closet Pole | LTIM 232 |

Saw it by hand or with power

- Cuts and copes with precision with hand saws
- For power saws:
 - Use a 7.5 in. blade with 24 teeth, or a 10 in. blade with 80 - 90 teeth
 - Make a quick cut for precision



Shoot it

- Hand nail with #3 or #4 bright finish nails
- With a nail gun, use:
 - 16 or 18 gauge finishing brads
 - Set pressure between 70 and 90 PSI

Find it in the Moulding Aisle at



Glue it

- You can expect excellent results with:
- PL Premium Polyurethane Construction Adhesive
- Liquid Nails® Paneling Wood & Foam Molding (LN-606)
- Liquid Nails® POLY(LN-950)



Caulk it

- Use a flexible latex based caulk
- We suggest products such as DAP:
 - Elastopatch™
 - Dynaflex™ 230
 - Kwik Seal™



Paint it

- Use any water based interior paint
- For long-lasting results, consider using a primer, which will help your final coat of paint adhere longer

PL is a registered trademark of Henkel Consumer Adhesives
Liquid Nails is a registered trademark of Macco Adhesives
Elastopatch™, Dynaflex™ 230 or Kwik Seal™ are trademarks of DAP Products Inc.
Gripper is a registered trademark of The Glidden Company doing business as ICI Paints